

**EU- Produktdatenblatt nach DELEGIERTER VERORDNUNG (EU) Nr. 65/2014 DER KOMMISSION vom 1. Oktober 2013 und DELEGIERTER VERORDNUNG (EU) Nr. 66/2014 DER KOMMISSION vom 14. Januar 2014**

|                                                                                            |               |
|--------------------------------------------------------------------------------------------|---------------|
| Name oder Marke des Herstellers                                                            | SMEG S.P.A.   |
| Produktkennzeichnung                                                                       | KT110BLE      |
| Annual Efficiency Consumption (AEC <sub>hood</sub> )                                       | 59.4 kWh/year |
| Energy efficiency class (EEC)                                                              | A             |
| Fluid Dynamic Efficiency (FDE)                                                             | 30            |
| Fluid Dynamic Efficiency class (FDEC)                                                      | A             |
| Lighting Efficiency (LE)                                                                   | 102.3 lux/W   |
| Lighting Efficiency Class (LEC)                                                            | A             |
| Grease Filtering Efficiency (GFE)                                                          | 76.6 %        |
| Grease Filtering Efficiency Class (GFEC)                                                   | C             |
| Air flow at minimum speed (Q <sub>min</sub> )                                              | 334 m³/h      |
| Air flow at maximum speed (Q <sub>max</sub> )                                              | 567 m³/h      |
| Air flow at boost speed (Q <sub>boost</sub> )                                              | 788 m³/h      |
| Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE <sub>min</sub> ) | 55 dB(A)      |
| Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE <sub>max</sub> ) | 63 dB(A)      |
| Airborne acoustical A-weighted sound power emission at boost speed (SPE <sub>boost</sub> ) | 70 dB(A)      |
| Power Consumption in Off mode (P <sub>o</sub> )                                            | 0             |
| Power consumption in stand-by mode (P <sub>s</sub> )                                       | 1 W           |
| Time increase factor (F)                                                                   | 1             |
| Energy Efficiency Index (EEI)                                                              | 52            |
| Measured air flow rate at best efficiency point (Q <sub>bep</sub> )                        | 438 m³/h      |
| Measured air pressure at best efficiency point (Q <sub>bep</sub> )                         | 434 Pa        |
| Measured electric power input at best efficiency point (W <sub>bep</sub> )                 | 176 W         |
| Normal Power of the light system (W <sub>l</sub> )                                         | 2 W           |
| Average illumination of the light on the cooking surface (E <sub>middle</sub> )            | 225 lux       |
| Sound power level at highest setting (L <sub>wa</sub> )                                    | 63 dB(A)      |

Dienstag, 26. Januar 2016